


Model		LTK65V100	LTK75V100	LTK86V100
Product picture	 			
General				
Diagonal display size		65(inch)	75(inch)	86(inch)
Bezel color	Aluminum frame(Black color)	√	√	√
Panel type	Ultra HD Direct type LED	√	√	√
Active area (mm)		1428.48 (H) * 803.52 (V)	1649.66 * 927.93(V)	1895.04 * 1065.96(V)
Resolution	3840*2160 /60hz	√	√	√
Pixel Pitch		0.372mm x 0.372mm	0.429 mm x 0.429 mm	0.4935 mm x 0.4935 mm
Hardness Glass	Mohs-7 level	√	√	√
Glass Panel	Anti-Glare glass with zero bonding	√	√	√
Aspect Ratio	16:9	√	√	√
Contrast Ratio	1200:1 (type)	√	√	√
Brightness	400cd/m2	√	√	√
Color depth	1.07 Billion Colors	√	√	√
Viewing angle	178°	√	√	√
Lifespan	50,000 hours	√	√	√
Touch type				
Touch Technology	IR touch	√	√	√
Multi Touch	Max 40 points(Windows)	√	√	√
Touch Precision	1 mm (over 90% Area)	√	√	√
Auto-Calibration	Yes	√	√	√
Anti-light	Yes	√	√	√
Minimum object size	2mm	√	√	√
Touch Response Time	First Point <2 ms, Continuation <8 ms	√	√	√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√	√	√
Sound				
Front Speakers	15W*2 (20W*2 option)	√	√	√
Subwoofer	20W*1 option	√	√	√
Total Power Amplifiers	≤60w	√	√	√
microphone (optional)				
microphone type	Linear equally spaced array microphone	√	√	√
mic number	8 array of mic	√	√	√
auto switch to op	yes	√	√	√
camera(optional)				
camera(optional)	48M/50M/ 64M	√	√	√
maximum resolution	8000*6000@5fps 4200*3120@20fps 3840*1920@30fps	√	√	√
lens	D=119 H=97 V=74	√	√	√
front port				
front port	Type-C * 1 line; HDMI IN * 1 line; USB3.0*3; USB-B*1			
7 button	Power on/off; Signal source; Setting; ECO; HOME; Volume down; Volume up			

rear port				
HDMI OUT	1	√	√	√
RJ45(LAN IN)	1	√	√	√
RJ45(LAN OUT)	1	√	√	√
AV IN	1	√	√	√
YPBPR	1	√	√	√
MIC IN	1	√	√	√
Earphone	1	√	√	√
Touch USB	1	√	√	√
VGA Audio IN	1	√	√	√
VGA IN	1	√	√	√
PDIF OUT	1	√	√	√
HDMI	2	√	√	√
DP	1	√	√	√
Android USB 3.0	1	√	√	√
Android USB 2.0	1	√	√	√
TF CARD	1	√	√	√
WIFI	WIFI5+WIFI6	√	√	√
BT	5.3	√	√	√
motherboard				
Android Version	14	√	√	√
Chip	GK6780V100	√	√	√
CPU	8*A55,1.8GHZ	√	√	√
GPU	Mali-G52 MP2(2EE)	√	√	√
NPU	5T	√	√	√
RAM	4G、8G	√	√	√
Flash	32G、64G、128G	√	√	√
Compliant with	Windows; Mac; Linux; Chrome OS	√	√	√
Over-the-Air Updates (OTA)	yes	√	√	√
air sensor	yes	√	√	√
central information				
Power Supply	~ 100-240 V (50/60Hz)	√	√	√
Standby Energy Consumption	≤ 0.5 W . H	√	√	√
Power Consumption		Maximun< 290W Eco<75W	Maximun< 320W Eco<75W	Maximun< 350W Eco<75W
Net Weight	(KG±2)	45	55	70
Gross Weight	(KG±2)	55	68	85
Screen Dimensions	(WxDxH)	1470.9 *97.5* 897.5 mm	1692.1 *97.5*1021.9 mm	1943.4*97.5*1166 mm
Dimensions Package	(WxDxH)	1594*1005*170MM	1818*1120*165	2055*1272*168mm
VESA Standard	(mm)	600*400 mm	600*400 mm	800*600 mm
Certifications	Ce,FCC,Rosh	√	√	√
Warranty	ONE year for the whole product and THREE years for touch parts by default. (can be extended, it's for an option)	√	√	√
Environmental conditions				
Operating Temperature	0℃ - 40℃ /32 - 100 °F	√	√	√
Storage Temperature	-20℃ - 60℃ /-4 - 140 °F	√	√	√
Storage Humidity	10 % - 90 %	√	√	√
Usage Humidity	10 % - 90 %	√	√	√
Accessories				
Accessories	WIFI antenna*4pcs, No ink pen * 2pcs, Remote control *1pc, 1.5m power cord *1pc, 1.5m HDMI cable *1pc, 1.5m USB touch cable *1pc; wall mount kit			